



## /AIRFOM – JET

### Cannons that are small, simple and effective

Cannon consisting of a tank and a CRONO fire valve equipped with an elastomer cup shaped obturator.

Activated using a special solenoid valve located on board the machine or in close proximity.

Ideal for use in areas where small obstructions are formed such as pipes, chutes, ducts, small dust deposits, et.



#### Technical Specifications

$P_{max} = 10\text{bar}$


Areas of application:

**ZF** (-10°C, +60°C) → cold zones, up to room temperature

**ZC** (-10°C, +100°C) → hot zone (ZC area limitations requires a feasibility assessment by our Technicians)



### /JET AIRCANNON

item	DN	Tank lt.	PS bar	TS Min / Max °C	X mm	Y mm	ZF	ZC	HT
610185	19	4	10	-10 +60	220	265	●		
610188	19	6	10	-10 +60	220	317	●		
610201	19	4	10	-10 +100	220	265		●	
610203	19	6	10	-10 +100	220	317		●	



### TANKS FOR /JET AIRCANNONS

item	Description	DN	Capacity lt.	Diameter Øe mm	Height h mm
610053	JET TANK 4 LT	20	4	220	170
610057	JET TANK 6 LT	20	6	220	222



/JET							
Volume Lt.	DN	Øe mm	A mm	B mm	C mm	D mm	E mm
4	20	220	220	265	170	95	89
6	20	220	220	317	222	95	89