



/AIRFLASH® COMPONENTISTICA DI IMPIANTO DEDICATA / AIRFLASH® DEDICATED COMPONENTS

STORM

VALVOLA DI ATTIVAZIONE MULTIPLA

*Soluzioni easy, smart e competitive
Per semplificare la gestione di impianto*

Valvola di attivazione multicannone (fino a max 6 cannoni) per lo sparo simultaneo.

STORM è dotabile di elettrovalvola con temporizzatore per la programmazione dei cicli di sparo.

Elettrovalvola di comando può essere connessa direttamente alla valvola STORM, oppure dislocata in box EV.

STORM

MULTIPLE ACTIVATION VALVE

*Easy, smart and competitive solutions
To simplify plant management*

Multi-aircannon activation valve (up to max 6 cannons) for simultaneous firing.

STORM can be equipped with a solenoid valve with timer for programming the firing cycles.

Activation solenoid valve can be placed directly on the STORM valve or in EV box.

STORM VALVOLA / VALVE

Code	DN	PS bar	TS Min / Max °C	ZF	ZC	VARIANTE VARIANT	NR. MAX CANNONI NR. MAX AIRCANNONS
600173	3/4"	10	-10 +80	•	•	CR	4U
600860	1"	10	-10 +80	•	•	CR	6U
600861	1"	10	-10 +80	•	•	CRKY	6U

Legenda

ZF [-10°C; +60°C]

ZC [-10°C; +80°C]



DIMENSIONALI / DIMENSIONS			
MODEL	DN	A mm	B mm
STORM DN20	3/4"	74	65
STORM DN25	1"	104	68

